

## Truck Series Diesel Performance and Protectant



### Description

An effective mixture of additives that clean and maintain diesel fuel systems. Prevents corrosion, increases lubrication thus reduces fuel pump and injector wear. Increases Cetane value for improved engine performance, easier starting and lower emissions. Regular use keeps the fuel system in perfect working order.

### Properties

- removes undesirable residues
- prevents the build-up of deposits
- protects expensive components against wear and corrosion
- increases smooth operation
- boosts the cetane number
- reduces pollutant emissions

### Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in liquid carrier
Color / appearance	hellbraun, klar / light brown, clear
Regulation on Flammable Liquids Class (Germany)	A III
Flash point	145 °F
Pour point	- 97 °F
Form	flüssig / liquid
Odor	charakteristisch / characteristic

### Areas of application

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF).

### Application

Contents (500 mL) is sufficient for 25–150 Liters (7 gal. to 40 gal.) diesel. Effect lasts up to 2000 km (1200 miles).

### Comment

 **WARNING:** Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### Available pack sizes

500 ml Can sheet metal 20254  
USA (-EN-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**